

OzoneSystems

Disinfect your water naturally

- UV And CD Technology Options
- Lower Energy Consumption
- Convertible Power: 110-240 VAC/50-60 Hz
- Less Inventory Needed With Universal Power Supply
- Family Of Ozonators Designed Specifically For The Hot Tub Environment





OzoneSystems

More Flexibility with More Choices

The O_3 zone family of ozonators were designed by Balboa, the leader in reliability in spa controls for over 20 years. These compact sanitizers were created specifically to withstand the demanding environment of the hot tub. Take your choice of Corona Discharge (CD) or Ultraviolet (UV) technology and rest assured that you have a comprehensive and reliable source of naturally disinfecting ozone.



Our new chip technology ozonator produces up to 20% more ozone than comparable models. A lower power draw represents a savings of up to 37% less energy and with twice the precious metals and twin emitters, it is one reliable ozone generator.



Our compact and polymer cartridge ozonator has a smaller footprint than most units and saves energy as well. It also features an extra fuse that protects from local failure and backs up the fuse on the controller board. This sealed unit is protected from harsh corroding environments and produces stable ozone output over a wide range of temperatures.

O₃zone UV Electronic Ballast

Our UV lamp ozone with PlasmaCellTM yields higher, consistent ozone levels using 1/3 the energy of conventional UV generators. In addition, the SmartStartTM solid-state electronic ballast eliminates start-up flicker, sputter, electronic noise and GFCI tripping.







| O₃zone Family | | | |
|-------------------------------------|---|-----------------|--------------------|
| Model | CD Cartridge | CD Chip | UV |
| Ozone (mg/hr @ 2 lpm) | 75 | 50 | 30 |
| Ozone (ppm) | 390 | 250 | 125-163 (CE/UR) |
| Dimensions (inches) | 5 x 6.375 x 2.67 | 5.5 x 7.5 x 3.0 | 12.75 x 2.4 x 2.78 |
| Max Spa Size (gal) | 1000 | 700 | 500 |
| Ams (typical) | 0.5 | 0.5 | 0.4 |
| Power Usage (watts) | 8.5 | 6.5 | 30 |
| Housing | Plastic | Plastic | Plastic |
| Approvals | CUR/UR,CE,RoHS | CUR/UR,CE,RoHS | UR,CE |
| Power Supply (110-240 VAC 50/60 Hz) | Universal | Universal | Convertible |
| Warranty* | 1 Year | 1 Year | 1 Year |
| Install Kit | Plastic Tubing, Check Valve, 4 Pin Amp Connector | | |

