



Fixciment

- Fast-setting fixing cement
- Good flexibility and compressive strength even after a short period.
- Contains no chloride, no corrosive effect.
- For fast fixing with early ability to withstand loading e.g. for:
 - 1) Insertion of door frames and iron gates.
 - 2) Fixing masonry screws, dowels, wall hooks and pipe clamps.
 - 3) Fixing balcony rails and stair rails, plumbing and electrical equipment.
- For sealing drainage points e.g. in brickwork, when using concrete and stoneware pipes.
- Setting time 3-5 minutes, ideal for remedial repairs.
- Suitable for indoor and outdoor use.
- Mix with water in the ratio 3 parts Fixciment, 1 part water.

Contents	Art. No:	Pack/Qty
5kg	0890 350	1



Solvent Cement

- For bonding PVC and ABS pipe work.
- A thixotropic solvent cement conforming to BS 6209
- Designed for spigot and socket bonding of non-pressure thermoplastic pipe systems such as PVC and ABS.
- Comes with brush applicator fixed to lid.
- Colour: Clear white
- Shelf life: 12 months.

Bonding Instructions:

Surface Preparation

Cut pipe clean & square. Remove any burrs and file a lead chamfer of approx 3mm at 15°. Roughen the mating surfaces with a medium grade emery cloth.

Clean the abraded surfaces.

Application

Solvent cement must not be stirred. Using a clean, flat brush apply an even layer of cement to both surfaces.

Bonding

Immediately push the spigot into the socket. Hold the joint for 10 seconds and wipe all excess. Joints should not be disturbed for 10 minutes, after which they may be handled with care.

Contents	Art. No.	P/Qty
250 ml	1893 214 072	1/10