# CLEANER CLEANSING AGENT FOR (RIGID) PVC, PVC-C AND ABS





#### STORAGE CONDITIONS

At least 36 months, if stored in a well-closed packaging in a dry place at a temperature between  $+5^{\circ}$ C and  $+25^{\circ}$ C. Limited shelf life after opening.

#### PRODUCT DESCRIPTION

Cleansing agent for (rigid) PVC, PVC-C and ABS.

# **FIELD OF APPLICATION**

For cleaning and degreasing piping, sleeves and fittings made of (rigid) PVC, PVC-C and ABS. Also suitable for removing uncured adhesive residue and for cleaning brushes and tools. Use in combination with the Griffon Cleaner Cloth. Not suitable for the dilution of PVC, PVC-C and ABS cement.

### **PROPERTIES**

- · Universal
- · Very powerful cleaning properties

#### **APPLICATION**

**Coverage:** Indication of the number of connections per 1 L:

Ø	32	40	50	63	75	90	110	125	160	200	250	315
#	800	700	650	550	330	250	160	140	90	50	35	23

# **Directions for use:**

- 1. Apply cleaner to a clean, highly absorbent cloth.
- 2. Clean and degrease surfaceso be joined. (Griffon Cleaner Cloth).
- 3. Remove condensation with a clean cloth and allow to dry thoroughly. Seal packaging carefully immediately after use.

# **TECHNICAL SPECIFICATIONS**

Chemical base: Mixture of solvents.

**Colour:** Transparent **Viscosity:** approx. 1 mPa.s. **Density:** approx. 0.82 g/cm<sup>3</sup> **Flash point:** K1 (<21°C)

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.