

Hydro-Pro On/Off	Model	P6/32	P8/32	P12/32	P14/32	P20/32	P23/32	P23T/32	P26T/32	
Part nr.		7024524	7024525	7024526	7024527	7024528	7024529	7024530	7024531	
Heating capacity A27/W27	kW	5.81	8.31	11.5	13.5	19.5	23.1	23.1	25.8	
Heating capacity A15/W25	kW	4.12	5.71	7.8	9.8	13.8	16.2	16.2	19.1	
Heating capacity A10/W25	kW	3.41	4.98	6.92	9.18	11.84	13.51	13.51	16.23	
Heating capacity A5/W25	kW	2.86	4.18	5.81	7.71	9.94	11.34	11.34	13.63	
Power input	kW	0.97	1.32	1.7	2.17	2.87	3.2	3.2	3.75	
Swimming pool volume*	m ³	20 - 30	30 - 40	40 - 55	50 - 70	70 - 95	80 - 115	80 - 115	95 - 135	
Running current	A	4.49	5.92	7.78	9.93	12.8	14.65	6.23	7.30	
Slow fuse current			15		20		35		20	
COP at A27/W27		5.87	6.34	5.90	5.74	6.30	6.42	6.42	6.29	
COP at A15/W25		4.25	4.33	4.59	4.52	4.81	5.06	5.06	5.09	
COP at A10/W25		4.31	4.34	3.6	4.4	4.09	4.53	4.53	4.51	
COP at A5/W25		3.66	3.69	3.07	3.74	3.49	3.85	3.85	3.84	
Power supply	V/Ph/Hz	230/1/50						380/3/50		
Condensor		Titanium								
Compressor type		Rotary								
Compressor brand		Hitachi			Mitsubishi		Gree			
Refrigerant		R32								
Fan quantity		1					2			
Fan direction		Horizontal								
Fan rotate speed	rpm	850	850	850	850	850	850	850	850	
Fan power input	W	90	90	120	150	150	120x2	120x2	120x2	
Noise (1m)	dB(A)	50	52	54	54	57	58	58	58	
Noise (10m)	dB(A)	38	42	42	42	45	46	46	46	
Water connection	mm	50mm								
Nominal flow volume	m ³ /h	2.3	3	4.5	5.3	6.8	7.5	7.5	9	
CO2 equivalent	ton	0.27ton	0.41ton	0.44ton	0.52ton	0.81ton	1.08ton	1.11ton	1.18ton	
Nett dimensions LxWxH	mm	770x315x585	953x360x605	953x360x605	1115x470x870	1115x470x870	1002x455x1250	1002x455x1250	1002x455x1250	
Shipping dimension LxWxH	mm	846x360x590	1070x450x630	1070x450x630	1210x510x880	1210x510x880	1210x495x1295	1210x495x1295	1210x495x1295	
Net weight/shipping weight	kg	37/47	50/67	59/76	82/97	86/105	116/134	116/134	120/138	

*provided it is correctly insulated, calculation model: min vol 5x heating capacity (A15/W25)
max vol 7x heating capacity (A15/W25)

Winter cover included